

FEATURES

- Exterior Dimensions (WDH): 635 x 595 x 1070 mm
- Internal Volume: 161 L
- Footprint: .37 sq.m.
- Dynamic LED Lighting In Door Provides Enhanced Product Illumination While Greatly Reducing Energy Consumption
- Forced Air Refrigeration System For Fast Product Temperature Pull Down
- High Impact Side Panel Graphics
- High Density Environmentally Friendly Insulation
- Utilizes Climate-Friendly Natural Refrigerant
- 2 Adjustable Powder-Coated Metal Shelves
- Self-Closing Acrylic Lid
- Top Basket Merchandises Single Layer of Promo Product
- Double-Paned, Low "E", Self-Closing Front Door
- Durable Pre-Painted Steel Cabinet and Heavy Duty Inner Liner
- Adjustable Temperature Control
- 9' Heavy Duty Power Cord



CERTIFICATIONS

220-240V/60Hz







- CE
- CB Scheme
- ROHS
- EU Energy
- EMC







TECH SPECS

Refrigerant R600a 1.4 **Amps**

220-240V/50Hz Volts/Hz

Compressor HP 1/6

DIMENSIONS

Exterior (WDH) 635 x 595 x 1070 mm Interior (WDH) 534 x 411 x 659 mm

Shelf (WD) 512 x 391 mm

Internal Volume 161 L

SHIPPING SPECS

Gross Weight 68 kg

Net Weight 58 kg

Carton Dims (WDH) 696 x 632 x 1110


Units per Pallet

Shipping Options 40'HQ ~108

53' ~ 144


IMMEDIATE CONSUMPTION COOLER







PACKOUT CAPACITIES

			Facings		Deep	Total Capacity	Total Rows
	355ml Can	3 Shelves	8	х	5	= 160*	4
		Base	8	х	5		
	Top Basket Vertical Option		7	х	2	= 14	1
Mileto Mi	Horiz	ontal Option	3	Х	5	= 15	1
	SOOml Com	2 Shelves	8	Х	5	= 120	3
		Base	8	Х	5		
	A	Top Basket	7	Х	1		
	S91ml PET	1 Shelf	7	Х	4	= 63**	2
	189	Base	7	Х	4		



^{*} Additional shelves, beyond what is supplied with the cooler, may be required to achieve this maximum pack-out.











^{** 20}oz pack-outs may vary depending on package size. Info based on sample.