

GCG-26c

UPRIGHT COOLER

G-Series Coolers



FEATURES

- Exterior Dimensions: 30.5"W x 30.5"D x 79"H
- High Visibility LED Illuminated Glass Door
- Dynamic LED Lighting In Door Provides Enhanced Product Illumination While Greatly Reducing Energy Consumption
- Forced Air Refrigeration System For Fast Product Temperature Pull Down
- High Density Environmentally Friendly Insulation
- High Impact Side Panel Graphics & LED Illuminated Canopy
- 5 Fully Adjustable Powder-Coated Metal Shelves
- Double-paned, Low "E", Self-Closing Glass Door
- Adjustable Temperature Control
- 9' Heavy Duty Power Cord
- Available in Climate-friendly Natural Refrigerant
- CETL & ETL Listed
- Conforms to NSF-7 Level 2
- ENERGY STAR® Qualified



8825 Boston Place, Rancho Cucamonga CA 91730 | Toll: 877.307.2665 | Office: 909.447.8254 | Fax: 909.305.8756 | www.idw.global

The specifications contained herein are for illustrative marketing purposes only and are not intended to be relied upon in whole or in part. All creative works are the sole property of IDW, Inc. Any reproduction in part or as a whole without written permission from IDW, Inc. is prohibited.

GCG-26c

UPRIGHT COOLER

G-Series Coolers

TECH SPECS

Refrigerant	R134a	R290
Amps	6.6	5.5
Volts/Hz	110-120V/60Hz	110-120V/60Hz
Compressor HP	1/2	1/3

SHIPPING SPECS

Gross Weight	289 lbs/131 kg
Net Weight	234 lbs/106 kg
Carton Dims (WDH)	31"x31"x87"/787x787x2210mm
Units per Pallet	1
Shipping Loads	40'HQ ~ 45 53' ~ 60

EXTERIOR DIMENSIONS

(WDH)	30.5" x 30.5" x 79" inches
	775 x 775 x 2007 mm

SHELF DIMENSIONS

(WD)	26" x 23.25" inches
	660 x 591 mm

PACKOUT CAPACITIES

	Facing	Depth	Shelves	Rows	Total Capacity
12OZ CAN	10	8	8	8	730*
	10	9	0	1	
16OZ CAN	10	8	6	6	570*
	10	9	0	1	
20OZ PET	9	8	4	5	360

* Additional shelves, beyond what is supplied with the cooler, may be required to achieve this maximum pack-out.



External Dimensions

Internal Dimensions

