

G-14c

DOUBLE DOOR COOLER

G-Series Coolers

FEATURES

- Exterior Dimensions: 30.5"W x 32"D x 58.5"H
- Dynamic LED Lighting In Door Provides Enhanced Product Illumination While Greatly Reducing Energy Consumption
- Forced Air Refrigeration System For Fast Product Temperature Pull Down
- High Impact Side Panel Graphics & LED Illuminated Canopy
- High Density Environmentally Friendly Insulation
- Utilizes Climate-Friendly Natural Refrigerant
- 8 Fully Adjustable Powder-Coated Metal Shelves
- Double-Paned, Low "E", Self-Closing Glass Door
- LED Interior Lighting
- Durable Pre-Painted Steel Cabinet and Heavy Duty Inner Liner
- Adjustable Temperature Control
- 9' Heavy Duty Power Cord

CERTIFICATIONS

110v

- CETL & ETL Listed
- NSF-7



Intertek



8825 Boston Place, Rancho Cucamonga CA 91730 | Toll: 877.307.2665 | Office: 909.447.8254 | Fax: 909.305.8756 | www.idw.global

The specifications contained herein are for illustrative marketing purposes only and are not intended to be relied upon in whole or in part. All creative works are the sole property of IDW, Inc. Any reproduction in part or as a whole without written permission from IDW, Inc. is prohibited.

G-14c

DOUBLE DOOR COOLER

G-Series Coolers

TECH SPECS

| | |
|---------------|-------|
| Refrigerant | R134a |
| Amps | 5.6 |
| Volts/Hz | |
| Compressor HP | 1/4 |

SHIPPING SPECS

| | |
|-------------------|-------------------------------|
| Gross Weight | 287 lbs/130 kg |
| Net Weight | 254 lbs/115 kg |
| Carton Dims (WDH) | 32"x31"x63.25"/813x787x1606mm |
| Units per Pallet | 1 |
| Shipping Loads | 40'HQ ~ 42 53' ~ 60 |

DIMENSIONS

External: 30.5"W x 32"D x 58.5"H inches / 775 x 813 x 1486 mm

Shelf: 25.75"W x 21"D inches / 449 x 210 mm

PACKOUT CAPACITIES

| | Facing | Depth | Shelves | Rows | Total Capacity |
|----------|--------|-------|---------|------|----------------|
| 12OZ CAN | 10 | 8 | 5 | 6 | 480* |
| 16oz Can | 10 | 8 | 4 | 5 | 400 |
| 20oz PET | 9 | 7 | 4 | 4 | 252 |

*Additional shelves, beyond what is supplied with the cooler, may be required to achieve this maximum pack-out.

